



“RHS” Butterfly Trip Moldboard

“QUALITY by DESIGN”

- ▶ Trip moldboard design with 10 gauge brake formed skinplate 36” high at center tapering upwards to 54” (56” on 12’ length) at the discharge end.
- ▶ Moldboard reverses 35 degrees either side of the bulldoze position.
- ▶ Two 3-1/2” diameter bore by 16” stroke reverse cylinders.
- ▶ Two point level lift chain arrangement or roller level lift arrangement available.
- ▶ Oscillator bar with 1” flame cut ears on 31” centers.



- ▶ Ram reverse or worm gear reverse options.
- ▶ 1/2” by 8” C-1085 cutting edge.
- ▶ Cutting edge backer angle punched on 8” and 12” centers.
- ▶ Moldboard and curb shoes supplied standard.
- ▶ Optional carbide blades and carbide moldboard shoes.
- ▶ Optional mushroom shoes or 10” steel wheel caster assemblies available.

Model	Overall Length	Moldboard Height	Reverse Method	Cutting Edge Length	Moldboard Thickness
RHS132TM3654S	132”	36” Tapered to 54”	Hydraulic or Worm Gear	132”	10 Gauge
RHS144TM3656S	144”	36” Tapered to 56”		144”	10 Gauge

Everest Equipment Company
1077 Westmount
Ayer’s Cliff, Quebec J0B 1C0 CANADA

819-838-4257
819-838-5653 fax

wausau-everest.com

WAUSAU • EVEREST
HEAVY-DUTY SNOW & ICE CONTROL



Wausau Equipment Company, Inc.
1905 South Moorland Road
New Berlin, WI 53151-2321 U.S.A.

800-788-6066 ~ 262-784-6066
262-784-6720 fax

wausau-everest.com