



12 VDC PURE SINE INVERTER
700W | 1000W | LOW PROFILE



FEATURES

This pure sine unit is perfect for the journeyman that has burned up a few other brands of HF inverters. You don't have the room to compromise on size, but you can no longer afford to compromise on quality. The WA chassis has a low profile and will mount almost anywhere you have room in your truck cab.

- Engineered construction and cooling methods
- Thermally controlled cooling fan
- Enclosed DC cable connections
- LED indication of External power, Inverter power, Low input voltage, High temperature, & Overload Automatic electronic short circuit/overload protection
- Automatic over temperature shutdown Remote ON/OFF switch hookup
- GFCI outlet protection
- Output circuit breakers
- Automatic low battery shutdown at 10.5 VDC (with in-rush delay)

	SPECIFICATION	TYPE	12WA7N	12WA10N
OUTPUT	Waveform	Shape	Pure Sine Wave, <5% THD Typical	
	Continuous Power	Watts	700	1000
	Peak Power	Watts	1320	1920
	Voltage	VAC	120 ± 5%	
	Continuous Current	Amperes (AC)	5.8	8.3
	Peak Current	Amperes (AC)	11	16
	Frequency	Hz	60 Hz ± 0.05%	
INPUT	Motor Start Rating	hp	NA	NA
	Nominal VDC	VDC	12	
	Range VDC	VDC	10.5 - 20	
PROPERTIES	Current	Ampers (DC)	70	100
	Chassis	Size	WA	WA
	Warranty	Years	4 Years, Advance Replacement first 2 years	
	Temperature	Degrees	-20° to 60° (0° to 140° F)	
	Efficiency	Percent	Up to 88%	
	Weight	lbs.	23	25
	DIMENSIONS	L x W x H inches	10.6 x 12 x 4.15	10.6 x 12 x 4.15